



Übersicht lieferbarer Extrudierter PTFE-Rohre; Sonderformate auf Anfrage.

Schema of Extruded PTFE-tubes; special sizes on request.

D O.D. (mm)	d I.D. (mm)	Toleranz D Tolerance O.D. (mm)	Toleranz d Tolerance I.D. (mm)	Gewicht Weight (kg/m)	Länge Length 2000 mm
10	4	+0,5 -0	+0 -0,5	0,16	•
	5			0,15	•
	6			0,13	•
12	6	+0,5 -0	+0 -0,5	0,21	•
	8			0,18	•
14	6	+0,5 -0	+0 -0,5	0,32	•
	8			0,27	•
	10			0,22	•
15	6	+0,5 -0	+0 -0,5	0,37	•
	8			0,31	•
	10			0,26	•
16	6	+0,5 -0	+0 -0,5	0,43	•
	8			0,38	•
	10			0,31	•
	12			0,23	•
18	6	+0,5 -0	+0 -0,5	0,54	•
	8			0,48	•
	10			0,44	•
	12			0,40	•
20	6	+0,5 -0	+0 -0,5	0,70	•
	8			0,65	•
	10			0,60	•
	12			0,49	•
	14			0,43	•
22	6	+1,0 -0	+0 -1,0	0,78	•
	8			0,75	•
	10			0,71	•
	12			0,63	•
	14			0,57	•
	15			0,50	•
25	6	+1,0 -0	+0 -1,0	1,07	•
	8			1,05	•
	10			1,02	•
	12			0,95	•
	14			0,88	•
	15			0,83	•
	18			0,68	•
20	0,58	•			
27	10	+1,0 -0	+0 -1,0	1,34	•
	12			1,08	•
	15			0,90	•
	18			0,78	•
	20			0,65	•
28	15	+1,0 -0	+0 -1,0	1,09	•
	18			0,95	•
	20			0,86	•
30	8	+1,0 -0	+0 -1,0	1,58	•
	10			1,53	•
	12			1,46	•
	14			1,38	•
	15			1,32	•

D O.D. (mm)	d I.D. (mm)	Toleranz D Tolerance O.D. (mm)	Toleranz d Tolerance I.D. (mm)	Gewicht Weight (kg/m)	Länge Length 2000 mm
30	18	+1,0 -0	+0 -1,0	1,20	•
	20			1,06	•
	22			0,80	•
	25			0,71	•
32	10	+1,5 -0	+0 -1,5	1,75	•
	15			1,54	•
	20			1,34	•
	22			1,13	•
	25			1,03	•
35	10	+1,5 -0	+0 -1,5	2,00	•
	15			1,89	•
	18			1,77	•
	20			1,66	•
	22			1,38	•
	25			1,27	•
38	20	+1,5 -0	+0 -1,5	2,10	•
	25			1,56	•
	28			1,39	•
	30			1,17	•
40	10	+1,5 -0	+0 -1,5	2,68	•
	15			2,54	•
	20			2,35	•
	25			1,98	•
	30			1,56	•
	35			1,03	•
45	10	+1,5 -0	+0 -1,5	3,36	•
	15			3,23	•
	20			2,93	•
	25			2,69	•
	30			2,23	•
	35			1,82	•
	38			1,57	•
50	20	+1,5 -0	+0 -1,5	3,97	•
	25			3,50	•
	30			3,10	•
	35			2,54	•
	40			1,81	•
55	20	+2,0 -0	+0 -2,0	4,78	•
	25			4,49	•
	30			3,91	•
	35			3,48	•
	40			2,85	•
60	20	+2,0 -0	+0 -2,0	5,64	•
	25			5,36	•
	30			5,01	•
	35			4,50	•
	40			3,80	•
	45			3,00	•
65	25	+2,0 -0	+0 -2,0	6,65	•
	30			6,30	•
	35			5,83	•

D O.D. (mm)	d I.D. (mm)	Toleranz D Tolerance O.D. (mm)	Toleranz d Tolerance I.D. (mm)	Gewicht Weight (kg/m)	Länge Length 2000 mm
65	40	+2,0 -0	+0 -2,0	4,85	•
	45			4,10	•
	50			3,54	•
	55			2,74	•
70	30	+2,0 -0	+0 -2,0	7,25	•
	35			6,78	•
	40			5,96	•
	45			5,74	•
	50			4,61	•
	55			3,87	•
75	30	+2,0 -0	+0 -2,0	8,53	•
	35			7,94	•
	40			7,08	•
	45			6,55	•
	50			5,77	•
	55			4,69	•
	60			4,22	•
80	40	+2,0 -0	+0 -2,0	8,78	•
	50			7,04	•
	55			5,43	•
	60			5,32	•
	65			4,52	•
	70			3,32	•
85	50	+2,0 -0	+0 -2,0	8,62	•
	60			8,39	•
	65			5,60	•
	70			5,18	•
	75			4,04	•
90	50	+2,0 -0	+0 -2,0	10,51	•
	60			7,22	•
	65			7,06	•
	70			6,26	•
	75			4,99	•
	80			3,99	•
95	50	+2,0 -0	+0 -2,0	11,87	•
	70			•	•
	75			7,55	•
	80			5,53	•
	85			4,20	•
100	50	+3,0 -0	+0 -3,0	13,22	•
	60			12,02	•
	70			10,11	•
	80			7,08	•
	85			5,45	•
	90			4,68	•
105	80	+3,0 -0	+0 -3,0	8,59	•
110	80	+3,0 -0	+0 -3,0	10,26	•
	90			7,86	•
	100			5,47	•
120	80	+3,0 -0	+0 -3,0	14,02	•
	100			8,84	•

 Standardmaße Standard production
 Sondermaße Additional production

Genannte Gewichte dienen nur als Richtwerte
 Weights stated are for guide purposes only

Längentoleranzen Tolerance on length: +2%